

**REGAL<sup>®</sup>**  
**Classic<sup>®</sup> Emulsion**  
**Eggshell - For interior Use**  
**319**

A premium all acrylic quality paint that dries to an elegant eggshell lustre. Use on properly prepared plaster, concrete, masonry, bricks, gypsum board, wood and metal. It has no unpleasant odour and features a spatter-resistant formulation, fast dry and excellent covering qualities. Provides a mildew resistant coating. Provides a durable finish that is more washable than a flat paint. Suitable for schools, nurseries, hospitals, offices and other areas subject to above normal wear.


**Performance Features**

- All acrylic premium quality.
- Dries to an attractive eggshell finish.
- Contains mildewcide to control fungi.
- Spatter-resistant, low odourless.
- Easy application and clean up.
- Excellent opacity.
- Scrubbable and hard wearing.
- Cleans easily – resists staining.

**Colors :** White and over 3.500 tinted colors are available from the Moor-O-Matic Color System.

**Toxicity:** Formulated without lead or mercury

**Gloss Level:** 5-15 at 60 degree viewing angle.

**Performance Guide:****Weather Resistance**

No recommended for exterior use.

**Heat Resistance**

Softens above 65° C.

**Water Resistance**

Scrubbable. Allow 7 days after application for firm to cure.

**Abrasion Resistance**

Resists burnishing. Good stain removal.

**Solvent Resistance**

Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



**VOC (Volatile Organic Compounds):** EU limit value for this product category A/a type WB: Interior matt walls and ceilings (gloss <25@60°), 30 g/l (2010). This product contains max 29 g/l VOC

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
12 – 14 m <sup>2</sup> /L	36%	96 micrometres	35 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
2 hours to touch 12 hours to recoat	Passes 6mm mandrel	Do not thin	Brush, Roller , Spray

**Surface Preparation**

Surface to be painted must be clean, dry and free of grease, dirt, dust, flaking paint and mildew. Dull glossy areas by sanding. Apply two coats of 319 REGAL Aqua Velvet Emulsion after priming the surface as outlined below.

**New Plaster, Gypsum Board:** Prime with a full coat of 216 REGAL FIRSTCOAT, or 570 MOORESTYLE Alkyd Multi-primer.

**Masonry, Concrete, Bricks:** Prime with 182 SUPER SPEC. Stabilising Primer or 181 SUPER SPEC. Alkali-Resisting Primer.

**Previously Painted Surfaces:** If surface is sound, prime with 023 FRESH START Eco Primer. Fill nail holes and cracks and sand when dry. Patched surfaces should be spot-primed with 023 FRESH START Eco Primer. If previous coating is old porous lime, apply an overall coat of 182 SUPER SPEC. Stabilising Primer.

**New Wood:** Prime surfaces with 572 MOORESTYLE Alkyd Undercoat or 023 FRESH START Eco Primer.

**Application**

Stir paint thoroughly before use. Apply by brush, roller or spray. Use a short nap roller on smooth surfaces. Thin 5% with clean water only if necessary. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

**Clean Up**

Clean equipment in warm, soapy water after painting. Do not empty into drains or watercourses. Dispose of empty container responsibly and according to local legislation

**Precautions Health, Safety and Environmental Protection**

•If medical advice is needed, have product container or label at hand. •Keep out of reach of children. •Keep container tightly closed. •Do not get in eyes, on skin, or on clothing. •Avoid release to the environment. •Call a POISON CENTER or a doctor if you feel unwell. •Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. •Safety data sheet available on request. •Contains: mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-Benzisothiazol-3(2H)-one, 2-OCTYL-2H-ISOTHIAZOL-3-ONE, 3-Iodo-2-propynyl N-butylcarbamate. May produce an allergic reaction. •Contains a biocidal product with fungicidal & algicidal properties. Active ingredients: butylcarbamate-3-iodo-2-propynyl (55406-53-6), 2-octyl-2H-isothiazol-3-one (26530-20-1) and zinc pyrithione (13463-41-7) to protect the coating (film). Do not empty into drains. The residual water from cleaning of the working equipment must not get into the ground or into surface waters.

POISON CENTER TEL.: +302107793777

**Packaging and Storage**

**Sizes :** 1 litre, 2.5litres, 5 litres, 10 litres

**Flash Point:** none

**Storage:** not hazardous, no special requirements

