

MOORE'S®
K & B™ Kitchens and Baths
Mildewcide Primer
For interior Use
323

A high quality, 100% acrylic primer formulated to be used where mould and mildew growth is likely. It provides outstanding adhesion and sealing, and can be applied under acrylic or enamel paints as well as over new and previously painted surfaces. Recommended for use in bathrooms, kitchens and other areas that may be subject to high humidity. 323 MOORE'S K&B Mildewcide Primer spatter-resistant formula is odorless and easy to apply.


**Performance Features**

- For kitchens, bathrooms, laundries and inside areas subject to humidity and frequent cleaning.
- Contains a mildewcide to control fungal growth.
- Quick dry allows recoat same day.
- Spatter resistant application.
- Good adhesive to new and previously painted surfaces.
- Gives a smooth surface for high quality finish.
- Use under water or solvent borne finishes.

Colors: White. May be tinted with Moor-O-Matic colorants to light colors for additional hiding.

Toxicity: Formulated without lead or mercury

Gloss Level: Flat.

**Performance Guide:****Weather Resistance**

No recommended for exterior use.

Heat Resistance

Up to 60° C.

Water Resistance

Excellent Water Resistance.

Solvent Resistance

Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



VOC (Volatile Organic Compounds): 322 MOORE'S K&B Kitchens and Baths Mildewcide Primer: belongs to the category A/g WB (Primers). EU Limit: 30g/l (2010).

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
9 – 10 m ² /L	33%	111 micrometres	37 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
1 hour to touch 2 hours to recoat	Passes 6mm mandrel	5% water	Brush, Roller , Spray

Surface Preparation

Surface to be painted must be thoroughly clean, dry and free of dust, dirt, grease, loose material, flaking paint and mildew. Clean hard or previously painted surfaces thoroughly with detergent and water. Rinse well. Remove loose material by scraping and sanding.

NOTE: If mildew is present, remove with a commercial mildew wash, following manufacturer's directions and cautions. Apply one coat of 323 MOORE'S K&B Mildewcide Primer. Fill nail holes, cracks and areas needing repair, then spot prime these areas.

Application

Stir thoroughly before and during use. Apply by brush, roller or spray. Thin as 5% with clean water. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

Clean Up: Clean equipment in warm, soapy water promptly after painting.

Precautions Health, Safety and Environmental Protection

•If medical advice is needed, have product container or label at hand. •Keep out of reach of children. •Keep container tightly closed. •Do not get in eyes, on skin, or on clothing. •Avoid release to the environment. •Call a POISON CENTER or a doctor if you feel unwell. •Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. •Safety data sheet available on request. •Contains: mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-Benzisothiazol-3 (2H) -one, 2-OCTYL-2H-ISOTHIAZOL-3-ONE, 3-Iodo-2-propynyl N-butylcarbamate. May produce an allergic reaction. •Contains a biocidal product with fungicidal & algicidal properties. Active ingredients: butylcarbamate-3-iodo-2-propynyl (55406-53-6), 2-octyl-2H-isothiazol-3-one (26530-20-1) and zinc pyrithione (13463-41-7) to protect the coating (film). Do not empty into drains. The residual water from cleaning of the working equipment must not get into the ground or into surface waters.

POISON CENTER TEL.: +302107793777

Packaging and Storage

Sizes : 1 litre, 3 litres,

Flash Point: none

Storage: not hazardous, no special requirements

