

COLORSTYLE™ Flat Emulsion For Interior Use 515



A superior quality paint that produces a beautiful, uniform, flat finish on properly prepared plaster, concrete, bricks, masonry, gypsum board, and wood. It has no unpleasant odour and features easy application, a spatter-resistant formulation, fast dry, excellent covering qualities and soap and water cleanup. Deep colours in flat paints do not lend themselves to hard usage or washing because they have a tendency to scuff or burnish. For areas subject to excessive wear or rough handling, use 519 COLORSTYLE Eggshell Emulsion.


Performance Features

- Dries to a beautiful, decorative flat finish.
- Spatter-resistant, low odour.
- Easy application and clean up, quick recoat.
- Excellent opacity.
- Breathable film

Colors : White and over 3.500 tinted colors are available from the Moor-O-Matic Color System.

Toxicity: Formulated without lead or mercury

Gloss Level: 0-5 at 60 degree viewing angle.



Performance Guide:

Weather Resistance

No recommended for exterior use.

Heat Resistance

60° C.

Water Resistance

Washable. Allow 7 days after application for firm to cure.

Abrasion Resistance

Resists marring, less so in darker colors.

Solvent Resistance

Good resistance to white spirits. Sensitive to aromatic hydro carbons and alcohols.



VOC (Volatile Organic Compounds): EU Limit value for this product category A/a type WB: Interior matt walls and ceilings (gloss <25@60°), 30g/l (2010). This product contains max 29g/l VOC

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
11 - 12 m ² /L	44%	100 micrometres	44 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
1 hour to touch 2-4 hours to recoat	Passes 6mm mandrel	5% water	Brush, Roller , Spray

Surface Preparation

Surface to be painted must be clean, dry and free of grease, dirt, dust, flaking paint and mildew. Dull glossy areas by sanding. Apply two coats of 515 COLORSTYLE Flat Emulsion after priming the surface as outlined below.

New Plaster, Gypsum Board: Prime with a full coat of 192 Aqua Grip Eco Primer or 570 MOORESTYLE Alkyd Multi-primer.

Masonry, Concrete, Bricks: Prime with 182 SUPER SPEC Stabilising Primer or 181 SUPER SPEC. Alkali-Resisting Primer.

Previously Painted Surfaces: If surface is sound, prime with 023 FRESH START Eco Primer. Fill nail holes and cracks and sand when dry. Patched surfaces should be spot-primed with 023 FRESH START Eco Primer. If previous coating is old porous lime, apply an overall coat of 182 SUPER SPEC Stabilising Primer.

New Wood: Prime surfaces with 572 MOORESTYLE Alkyd Undercoat or 023 FRESH START Eco Primer.

Application

Stir paint thoroughly before use. Apply by brush, roller or spray. Use a short nap roller on smooth surfaces. Thin as 5% with clean water. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

Clean Up: Clean equipment in warm, soapy water.

Precautions Health, Safety and Environmental Protection:

If medical advice is needed, have product container or label at hand • Keep out of reach of children • Do not get in eyes, on skin, or on clothing • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). • May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes : 1 litre, 3 litres, 10 litres,

Flash Point: none

Storage: not hazardous, no special requirements

