


# MOORESTYLE™

## Wood & Metal Enamel

### Satin

### 577



A superb quality alkyd enamel that lasts for years indoors or out. Recommended for use on primed wood and metal surfaces. Features excellent application properties, quick dry, and durability. The low odour characteristics result in more pleasant interior application. Formulated without lead.


#### Performance Features

- Has superb levelling and hiding qualities.
- Excellent sag resistance.
- Hard wearing, durable, weather resistant.
- Low odour during application.
- Use on exterior and interior surfaces.
- Elegant satin finish.
- Suitable for high use or commercial areas.

**Colors:** White, black and over 3.500 tinted colors are available from the Moor-O-Matic Color System.

**Toxicity:** Formulated without lead or mercury.

**Gloss Level:** 25 - 30 at 60 degree viewing angle.



#### Performance Guide:

##### Weather Resistance

Good resistance to weathering.

##### Heat Resistance

Up to 120°C. Continuous heat will cause premature yellowing and embitterment.

##### Water Resistance

Good resistance to water and condensation. Scrubbable

##### Abrasion Resistance

Excellent resistance to abrasion.

##### Solvent Resistance

Good resistance to aliphatic solvents and alcohols. Sensitive to aromatic hydro carbons and other strong solvents.



**VOC (Volatile Organic Compounds):** This product belongs to the category A/d SB: Interior/Exterior trim and cladding paints for wood and metal. Ready to use product contains maximum 299g/L which is under the relevant EU limit values: 300g/l (2010).

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
15 - 16 m <sup>2</sup> /L	42%	72 micrometres	30 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
3 hours to touch 16 hours to recoat	Passes 3mm mandrel	5% low odour white spirits	Brush, Roller, Spray

#### Surface Preparation

Surface to be painted must be free of all loose material such as dust, flaking and peeling paint. The surface must be clean with all traces of grease, oil, and dirt removed. Remove loose material by scraping and sanding. Sand glossy surfaces to a dull finish. Apply two coats of 577 MOORESTYLE Satin Wood & Metal Enamel after priming as outlined below.

**New Wood:** Spot prime all caulked nail holes and patches with 572 MOORESTYLE Alkyd Undercoat. Allow to dry, then apply a full coat of Alkyd Undercoat. Sand to a smooth surface.

**New Plaster, Gypsum Board:** Prime with 192 AQUA GRIP Eco Primer or 570 MOORESTYLE Alkyd Multi-primer.

**Ferrous Metal:** Remove rust and loose material before priming exposed metal with 568 MOORESTYLE Rust Primer.

**Previously Painted Surfaces:** Prime with 570 MOORESTYLE Alkyd Multi-primer.

#### Application

Stir thoroughly before and during use. Apply by brush, roller or spray. Thin 5% with low odour white spirits. Do not apply when air or surface temperature is below 10°C or when the humidity is high. Drying times are longer under cool/moist conditions.

**Clean Up:** Clean brushes and equipment with white spirits.

#### Precautions Health, Safety and Environmental Protection:

**CAUTION.** Contains - Naphtha (petroleum), heavy hydrogenated • Flammable liquid and vapour. • Harmful to aquatic life with long lasting effects. • Repeated exposure may cause skin dryness or cracking • May cause drowsiness or dizziness. IF INHALED: Remove person to fresh air and keep comfortable for breathing • Contains cobalt bis(2-ethylhexanoate) and 2-Butanone oxime. May produce an allergic reaction • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. • No smoking. • Do not get in eyes, on skin, or on clothing • Wear protective gloves, protective clothing, eye protection, face protection. • Call a POISON CENTER, doctor if you feel unwell. • Keep out of reach of children. • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Keep cool. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777



#### Packaging and Storage

**Sizes:** 0,75litre, 1litre, 2,5litres, 3litres

**Flash Point:** 44°C (Abel)

**Storage:** PAINTS, flammable liquid

